

LUX B1010 570 x 800 mm  
 LUX B1020 570 x 1100 mm

**Casing:**

<u>outer size</u>	<u>inner size</u>	<u>size including architrave</u>
570 x 800 mm	515 x 745 mm	610 x 840 mm
570 x 1100 mm	515 x 1045 mm	610 x 1145 mm

White plastic casing with integrated architrave has.  
 Case sides 22 x 74 mm

**Hatch:**

Frame	rebated plastic profile
Insulation	50 mm polystyrene.
Hatch surface	white plastic
Insulation factor	0,54 W/m <sup>2</sup> C°

**Surface treatment:**

Additional surface treatment is not required

**Fire rate:**

Unrated

**Locking:**

Espagnolette	440 mm long
Key/handle	round metal; diameter 9 mm, length 120 mm.
Measurement	square 7-8 mm.

**Sealing:**

Q-LON profile (QL-3005) is mounted between the casing and the trap door.

**Others:**

The wall hatch has the hinges placed against each other, which allows to place the dor either on the left or the right side.

The hinges and the lock are placed on the longer side of the hatch.

**Weight:**

<b>product</b>	<b>weight</b>	<b>number per pallet</b>
LUX B1010	10 kg	34
LUX B1020	13 kg	34